

G20 Carpentry/Timber Framing/First Fixing

950 CELLULAR PVC FASCIA/BARGES/SOFFITS

Material: [Cellular PVC \(PVC-ue\)](#)

Material Specification: [To BS7619:1993:Type1](#)

Manufacturer: [Swish Building Products, Tamworth, Staffordshire, B79 7TF](#)

Manufacturer accreditation:

- ISO 9001/2
- Class 1 Surface spread of flame to BS476 :Part 7 : 1987

FASCIA

Profile:⁽¹⁾ [C286 Jumbo Board \(175 x 20mm\)](#)

Finish/Colour: [White](#)

Support timber: [Fix to rafter ends](#)

Fixings:⁽²⁾ [C073 65mm A4 S/S Capped Screws](#)

Fixing centres: [600mm maximum](#)

Joints: [C153 Concealed Fix Jumbo joints](#)

BARGEBOARD

Profile: ⁽¹⁾ [C136 Cappair \(163mm\)](#)

Finish/Colour: [White](#)

Support timber: [Existing timber bargeboard](#)

Fixings: ⁽²⁾ [C082 50mm Trimtop S/S nails](#)

Fixing centres: [600mm maximum](#)

Box end details: ⁽⁵⁾ [As Fig 29, Page 21 Swish Specification Guide](#)

Joints: [C235 face fixed joint covers](#)

FASCIA SOFFITS

Profile : ⁽³⁾ [C308 Polo Board \(300mm\)](#)

Finish/Colour: [White](#)

Fixings : ⁽²⁾ [C081 40mm Trimtop A4 S/S nails](#)

Fixing Centres : [200mm max centres across width and 600mm max along length.](#)

Joints: [C041 Joint Trim.](#)

BARGEBOARD SOFFITS

Profile: ⁽³⁾ [C246 GeePee Board \(300mm\)](#)

Finish/Colour: [White](#)

Fixings: ⁽²⁾ [C081 40mm Trimtop A4 S/S nails](#)

Fixing Centres: [200mm max centres across width and 600mm max along length](#)

Joints: [C041 Joint Trim](#)

OVER-FASCIA VENTILATION/EAVES PROTECTION

⁽⁴⁾ [C502 Jumbotec & Eaves Ventilator Trays along full length of eaves](#)

Fixings: ⁽²⁾ [Galvanised clout nails](#)

Fixing centres: [200mm maximum](#)

Corners: [C403 Sealing Tape as necessary](#)

Sealing: [C403 Sealing Tape as necessary](#)

Fixing procedures as per Swish Roofline Design and Specification Guide [A227](#)

Notes :

⁽¹⁾ **Replacement, load bearing profiles:** Square Jumbo, Bullnose Jumbo or Ogee Jumbo.

Refurbishment overcapping profiles: Cappit or Cappair.

⁽²⁾ Specify A4 Marine Grade stainless steel nails or screws.

⁽³⁾ **Flat Boards:** Gee Pee, Gee Pee with appropriate strip ventilators, Polo (vented flat board). **Cladding as Soffit:** Tee Gee, Open V, or Polo (vented) versions of these.

⁽⁴⁾ **Eaves Protection:** Jumbotec (without ventilator). Vented Eaves Protector C404. **Eaves Ventilators only:** C504 & C505

⁽⁵⁾ **Boxend** detail drawings may be found on pages 15/16 of the Swish Design & Specification Guide [A227](#). They are also printable from the Swish website in Technical Centre> Installation Guidance> Box Ends.

Please quote Swish References in all cases.